

Swing gates

Secure enclosure

Various application varieties



The swing gate for safe access

Europa

With a closed Heras Europa, the swing gate is no longer the weakest link of the total fence; the Europa is a part of your fence that keeps trouble outside. Heras have developed various application varieties, heights and widths for the Europa concept. The Europa is available in both single and double-leaf configurations and is designed for quick and easy installation.

HERAS



Single-leaf swing gate



Double-leaf swing gate



Swing gate with Atlas infill



Swing gate with Heracles infill

Technical specifications

Gate Type	Number of gate leaves	Clear width	Height
EU 10	1	1,040	See note
EU 12	1	1,200	See note
EU 15	1	1,640	See note
EU 20	1	2,090	See note
EU 25	1	2,540	See note
EU 30	1	2,990	See note
EU 35	1	3,630	See note
EU 40	1	4,080	See note
EU 45	1	4,530	See note
EU 50	1	5,130	See note
EU 10 -10	2	2,020	See note
EU 12 -12	2	2,548	See note
EU 15 -15	2	3,220	See note
EU 20 -20	2	4,120	See note
EU 25 -25	2	5,020	See note
EU 30 -30	2	5,920	See note
EU 35 -35	2	7,205	See note
EU 40 -40	2	8,105	See note
EU 45 -45	2	9,005	See note
EU 50 -50	2	10,205	See note

Note: Height of gates: Heracles: 1.000 t/m 2.500 mm Atlas: 1.000 t/m 2.500 mm Athos: 1.000 t/m 2.500 mm Pallas: 1.500 t/m 2.000 mm Dimensions in mm.

Colour schemes

- Galvanised or coated. Standard coating, available as RAL 6005 (moss green), RAL 6009 (fir green), RAL 6014 (Heracles green), RAL 7016 (anthracite grey), RAL 7030 (stone grey), RAL 9005 (black) and RAL 9010 (pure white).
- As the RAL 9006 and RAL 9007 colours come in several variants they are only available - at a surcharge - if the additional 'variant' colour code is stated.
- Other RAL colours are available upon request

Coating

Galvanised and aluminium parts are pre-treated before coating. Electrostatic powder-coating is then applied, after which the coated materials are cured in an oven (210 °C) to create a durable coating with an average thickness of 80 µm and a hardness of 80 buchholz.

Standaarduitvoering	Opties
<ul style="list-style-type: none"> Universal connection to Heras fence The reinforced version has double top rails Heracles & Atlas: the centre-to-centre distance of the bars is 132 mm Athos: the centre-to-centre distance of the bars is 150 mm 	<ul style="list-style-type: none"> Drop bolt Ground slam set Electrical opener for pedestrian gates Gate closer for pedestrian gates The swing gate can be mounted to a wall Chain link in the gate leaves Emergency lock and aluminium plating Also in Orpheus

